

May cause chemical burns of the mouth, throat, and esophagus. Signs and symptoms will include pain or discomfort in the mouth, throat, chest, and abdomen, nausea, vomiting, diarrhea, dizziness, and drowsiness, faintness, weakness, collapse, and coma. In animal studies in rats and mice, NMP was embryotoxic by the oral and intra peritoneal routes at very high dose levels which were close to the LD50.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Preexisting eye, skin, and respiratory disorders, or preexisting impaired peripheral nerve function may be aggravated by exposure to this product.

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION EYE

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT:

Immediately flush eyes with water for at least 15 minutes. The eyelids must be held open and away from the eyeball to ensure that all surfaces are flushed thoroughly. Seek immediate medical attention, preferably an ophthalmologist.

SKIN CONTACT:

Wash affected area(s) with soap and water. Remove and launder contaminated clothing before reuse. If irritation develops, consult a physician.

INHALATION:

Remove to fresh air. Give artificial respiration, if not breathing. Oxygen may be given, if necessary. Call a physician.

INGESTION:

Rinse mouth with water. Give at least 2 glasses of water or milk at once, if the patient is conscious. **DO NOT** induce vomiting. Seek immediate medical attention.

SECTION VI - REACTIVITY DATA

STABILITY: UNSTABLE STABLE

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS:

Burning can produce nitrogen oxides, carbon monoxide, and carbon dioxide.

CONDITIONS TO AVOID:

Keep product away from heat, sparks, pilot lights, static electricity, and open flame.

INCOMPATIBILITY (MATERIALS TO AVOID):

Strong mineral acids and oxidizers.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities, if product has entered or may enter sewers, watercourses, or extensive land areas. Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, flammable vapors from absorbed material.

WASTE DISPOSAL METHOD:

Dispose of in accordance with local, state and federal regulations.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

Avoid prolonged or repeated breathing of vapors. If exposure may or does exceed occupational exposure limits use a NIOSH approved respirator to prevent overexposure.

VENTILATION:

If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits (see Section II), additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, systems safe for such locations should be used.

PROTECTIVE GLOVES:

The use of gloves impermeable to the specific material handled is advised to prevent skin contact, possible irritation and absorption.

EYE PROTECTION:

Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended.

OTHER PROTECTIVE EQUIPMENT:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

HYGIENIC PRACTICES:

Wash with soap and water.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep containers tightly closed. Keep containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. Use good personal hygiene practice. "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death. "Empty" containers should be completely drained, properly bunged and promptly shipped to the supplier or a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

OTHER PRECAUTIONS:

For industrial use only.

SECTION X - REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA STATUS:

All chemicals found in this product comply with the Toxic Substance Control Act inventory reporting requirements.

EPA SARA TITLE III CHEMICAL LISTINGS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

| CHEMICAL NAME: | CAS NUMBER: | CONCENTRATION: |
|------------------------|--------------------|-----------------------|
| Triethylamine | 121-44-8 | 1.0 % |
| N-methyl-2-pyrrolidone | 872-50-4 | 12.6 % |

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS PRODUCT OR INFORMATION, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. The information and product are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use thereof.