

## Superslip 6515AL

A highly engineered HDPE/EBS/aluminum oxide nanocomposite for maximum scratch, scuff and block resistance

### Features and Benefits

- Maximum scratch resistance; equal to PE/PTFE additives
- HDPE/EBS composite reinforced with 300 nm aluminum oxide nanoparticles (Mohs Hardness 9)
- Good abrasion resistance with slip and lubricity
- Amide wax component provides excellent antiblocking and release properties
- Ideal for can and container coatings; 21CFR 175.300 approved

### Composition

HDPE/EBS/aluminum oxide

### Recommended Addition Levels

0.5-1.5% (on total formula weight)

### Systems and Applications

Water based, solvent based and energy curable coatings and inks. Industrial coatings (including plastic and metal); stains, sealers and varnishes; wood coatings; printing inks and OPV's (including flexo and gravure); powder coatings; can, container, and coil coatings; rubber additives.

### Typical Properties\*

	<u>Superslip 6515AL</u>
<b>Melting Point ° C</b>	139 - 145
<b>Density @ 25 ° C (g/cc)</b>	0.99
<b>NPIRI Grind</b>	1.0 - 2.0
<b>Maximum Particle Size (µm)</b>	15.56
<b>Mean Particle Size (µm)</b>	3.5 - 5.5

This product is also available as a water based wax dispersion - Microspersion 6515AL-40

Feb-25