

# SYNTRAN<sup>®</sup> 3104

Technical Information

SYNTRAN<sup>®</sup> 3104 is based on a proprietary film-forming polymer technology. This technology improves the properties of adhesion, cohesion, gloss, flexibility, dispersion, and water resistance.

## Performances

---

<b>Applications</b>	Flexible and adhesive coatings
<b>Features and Benefits</b>	Excellent adhesion to multiple substrates High compatibility with other resins & additives Enhances pigment dispersion and provides binding properties Increases water resistance and gloss to your formulation

## Typical Chemical and Physical Properties (do not constitute specifications)

---

<b>Physical form</b>	White emulsion
<b>Solids content</b>	41.0%
<b>pH value</b>	7.5
<b>Viscosity</b>	< 500 cps
<b>Density @22°C</b>	1.033
<b>MFFT</b>	20°C
<b>Freeze-thaw stability</b>	Protect from freezing
<b>Stability at 52°C</b>	Unchanged after 30 days

## Safety, Storage, Handling

---

Please refer to Safety Data Sheet.  
Shelf life: 12 months from shipping date in originally sealed containers.  
Storage: between 5°C and 35°C.

April 20 / Page 1 of 1

The suggestions and data included are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. It is the buyer's responsibility to determine the suitability of the above formulation through quality control and field testing. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any existing or pending patents.