

# SYNTRAN<sup>®</sup> 6200

Technical Information

SYNTRAN<sup>®</sup> 6200 is based on high solids technology. This technology creates a film with very high flexibility, excellent water resistance, and excellent coverage. This technology also allows for excellent adhesion over multiple substrate types.

## Performances

---

### Applications

Textile and leather coatings  
Pigmented coatings and sealants  
Label, board and packaging coatings (OPV)  
Cement based formulation

### Features and Benefits

Film has very high flexibility with excellent water resistance  
High compatibility with pigments, waxes and other additives  
Excellent adhesion to flexible films and foils  
Zero VOC requirements to formulate coating

## Typical Chemical and Physical Properties (do not constitute specifications)

---

<b>Physical form</b>	White emulsion
<b>Solids content</b>	50.0%
<b>pH value</b>	8.0
<b>Viscosity</b>	< 500 cps
<b>Density</b>	1.023
<b>MFFT</b>	5°C
<b>Freeze-thaw stability</b>	Protect from freezing
<b>Stability at 52°C</b>	Unchanged after 30 days

## Safety, Storage, Handling

---

Please refer to Safety Data Sheet.

Shelf life: 12 months from shipping date in originally sealed containers.

Storage: between 5°C and 35°C.