

SYNTRAN® 6211

Technical Information

SYNTRAN® 6211 is based on high solids technology. This technology creates a film with very high flexibility, excellent water resistance, and excellent coverage. This technology also allows for excellent adhesion over multiple substrate types.

Performances

Applications	Interior & Exterior Paints Concrete Primers
Features and Benefits	Film has very high flexibility with excellent water resistance High compatibility with pigments, waxes and other additives Excellent adhesion to multiple substrates Zero VOC requirements to formulate coating

Typical Chemical and Physical Properties (do not constitute specifications)

Physical form	White emulsion
Solids content	50.0%
pH value	7.0
Viscosity	100 cps
Density	1.040
MFFT	< 0°C
Freeze-thaw stability	Protect from freezing
Stability at 52°C	Unchanged after 30 days

Safety, Storage, Handling

Please refer to Safety Data Sheet.
Shelf life: 12 months from shipping date in originally sealed containers.
Storage: between 5°C and 35°C.

April 20 / Page 1 of 1

The suggestions and data included are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. It is the buyer's responsibility to determine the suitability of the above formulation through quality control and field testing. Suggestions for uses of our products should not be understood as recommendations that they be used in violation of any existing or pending patents.